

ALM

a positive partnership

Rolled Lead Sheet Theoretical Weights Chart / KG

Width (mm)	Nearest Imperial (inch)	Code 3		Code 4		Code 5		Code 6		Code 7		Code 8	
		3m	6m	3m	6m	3m	6m	3m	6m	3m	6m	3m	6m
150	6	7	13	9	18	11	23	14	27	16	32	18	36
180	7	8	16	11	22	14	27	16	32	19	39	22	43
210	8	9	19	13	26	16	32	19	38	23	45	25	51
240	9	11	22	15	29	18	37	22	43	26	51	29	58
300	12	13	27	18	37	23	46	27	54	32	64	36	72
360	14	16	32	22	44	27	55	32	65	39	77	43	87
390	15	18	35	24	48	30	59	35	70	42	84	47	94
450	18	20	40	28	55	34	69	41	81	48	96	54	109
510	20	23	46	31	62	39	78	46	92	55	109	62	123
600	24	27	54	37	73	46	91	54	108	64	129	72	145
760	30	34	68	47	93	58	116	69	137	81	163	92	184
800	32	36	72	49	98	61	122	72	144	86	171	97	193
850	34	38	76	52	104	65	130	77	153	91	182	103	205
914	36	41	82	56	112	70	139	82	165	98	196	110	221
1000	39	45	90	61	122	76	152	90	180	107	214	121	242
1200	48	54	108	73	147	91	183	108	216	129	257	145	290
1600	63	72	144	98	196	122	244	144	288	171	343	193	386
2400	96	-	-	147	294	183	366	216	433	257	514	290	580
Thickness (mm)		1.32		1.80		2.24		2.65		3.15		3.55	
Kg/m ²		14.97		20.41		25.40		30.05		35.72		40.26	

All theory weights are subject to BS EN12588:06 (manufacturing tolerance of ± 5%), and calculated by: length(m)xwidth(m)xkg/m²



Also available

- Patination Oil**
- Flashpoint**
- Annular Ring Shank Nails**
- Cast Lead Domes**
- Lead Weathering Slates**
- Flexislates**
- Lead Expansion Joints**



Also available

- Fixing Clips**
- Fixing Strip**
- Wood Cored Roll**
- Underlays**
- Lead Sheet Restorers**
- Solders and Fluxes**
- Metwash**

Sales Line - 07000 1258806