



NOMINAL ROLL WEIGHTS

MACHINE CAST LEAD - EN14783:2013

WIDTH		CODE 3		CODE 4		CODE 5		CODE 6		CODE 7		CODE 8	
(MM)	(INCH)	3M/KG	6M/KG	3M/KG	6M/KG	3M/KG	6M/KG	3M/KG	6M/KG	3M/KG	6M/KG	3M/KG	6M/KG
150	6"	7	13	9	18	11	23	14	27	16	32	18	36
180	7"	8	16	11	22	14	27	16	32	19	39	22	43
210	8"	9	19	13	26	16	32	19	38	23	45	25	51
240	9"	11	22	15	29	18	37	22	43	26	51	29	58
300	12"	13	27	18	37	23	46	27	54	32	64	36	72
360	14"	16	32	22	44	27	55	32	65	39	77	43	87
390	15"	18	35	24	48	30	59	35	70	42	84	47	94
450	18"	20	40	28	55	34	69	41	81	48	96	54	109
510	20"	23	46	31	62	39	78	46	92	55	109	62	123
600	24"	27	54	37	73	46	91	54	108	64	129	72	145
760	30"	34	68	47	93	58	116	69	137	81	163	92	184
800	32"	36	72	49	98	61	122	72	144	86	171	97	193
850	34"	38	76	52	104	65	130	77	153	91	182	103	205
914	36"	41	82	56	112	70	139	82	165	98	196	110	221
1000	39"	45	90	61	122	76	152	90	180	107	214	121	242
1200	48"	54	108	73	147	91	183	108	216	129	257	145	290
1460	58"	66	131	89	179	111	223	132	263	156	313	176	353
THICKNESS (MM)		1.32		1.80		2.24		2.65		3.15		3.55	
WEIGHT PER M2		14.97		20.41		25.40		30.05		35.72		40.26	

LEAD FLASHINGS THEORY WEIGHTS: ALL THEORY WEIGHTS ARE SUBJECT TO ±5% TOLERANCE. THE THEORY WEIGHT OF LEAD SHEET IN KGS CAN BE CALCULATED USING THE FOLLOWING FORMULA: NO. OF PIECES X LENGTH IN METRES X WIDTH IN METRES X THICKNESS IN MM X 11.34

STANDARD FLASHINGS ARE SHOWN IN THE CHART ABOVE, ANY WIDTHS FROM 100MM (4") TO 1460MM (58") CAN BE PRODUCED.